

The Gateway is the link between the E-Line Swinghandles and the Ethernet LAN. It can handle up to 250 E-Line HID Swinghandles with addresses from 1 to 254, or up to 31 keypad Swinghandles. The Gateway is IP addressable and is the link between the user software and the handles.

- Connects enclosure swinghandles with the local area network
- Compatible with HID 485 Swinghandle locks with E-Line network protocol V3.

Part Number T2AC005-P

Physical

Shipping Dimensions (H x W x D)
9 x 9 x 4 inches

Shipping Weight
2 lbs.

Unit Weight
1.5 lbs.

Gateway

Status indicated by 2 multi-color lights
1 input jack for power (DC) with 2.1mm pin
3 connectors Modular Plug 8p/8p (RJ-45)
Real Time clock

Power Supply

Input Voltage 100 to 125 V AC, 50 to 60Hz, 0.3A
Input Connector: NEMA 1-15P
Output Voltage 12V DC / 780 mA (5%)
Output Connector 5.5 x 2.1mm circular
Operating Range 0° to 45°C, 20-90% RH

Function

Forwarding Lock events and control commands

Included components

Gateway
Power supply
Junction cable
SharkTRAC tool-less integration bracket

Conformance

UL1950 / CSA 22.2, EN60950
1 Year Warranty



Gateway



1-15P

Power Supply